

Boat Manufactured By:

BLUE+WAVE. 711 Boren Boulevard • Seminol, OK 74868

(405) 382-0349 www.bluewaveboats.com

BLUE WAVE 2800 PURE HYBRID

Length	27' 2"
Beam	9' 2"
Dry Weight (Boat Mfr. Pub)	3,650 lbs
Maximum HP	557 hp
Fuel Capacity	94 gal
Weight as Tested	6,600 lbs

F250XCA / LF250XCA

Horsepower	250 hp
Induction	EFI/VCT/DOHC
Displacement	4.2L
Weight (Estimated)	562 lbs
Gear Ratio	1.75:1

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#3
Ventilation Plate Height	10" Hydraulic Plates

PROPELLER(S)

Saltwater Series II™
15 x 21
6CE-45972-20-00 / 6CF-45972-20-00
Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	63° F / 65° F
Elevation (in feet above sea level)	0'
Wind Velocity	0-5 MPH

COMMENTS

Tested w/ 2 people, 70 gallons of fuel, two 10" hydraulic jackplates, 4 batteries, hard T-top, two 10' powerpoles, 36 volt trolling motor, safety and test equipment

YPB#: PB_BWB_2800PureHybrid_TW_F250XCA_02-26-19_BAY

PERFORMANCE BULLETIN



Engine: Yamaha F250XCA / LF250XCA Boat: Blue Wave 2800 Pure Hybrid Configuration: Twin Test Date: 26-Feb-2019



PERFORMANCE DATA

RPM	МРН	GPH	MPG
1000	6.4	2.7	2.36
1500	8.0	4.4	1.82
2000	9.5	7.8	1.21
2500	21.3	9.8	2.17
3000	31.4	12.7	2.48
3500	38.4	16.6	2.32
4000	43.9	22.9	1.92
4500	49.8	28.1	1.78
5000	55.4	36.8	1.51
5500	60.2	40.5	1.49
6050	65.6	50.9	1.29
0-30 MPH: 5.02 se	conds		

NOTICE TO CONSUMER The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's performance may be additive. Please confirm the specifications and performance data on your specific boat/engine combination with your dealer prior to purchase. Please allow performed the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.